

11-13-00

PTO/SB/05 (08-00)

Approved for use through 10/31/2002. OMB 0651-003

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

A  
11/10/00

JC84311S PTO

## UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.	36968/202435
First Inventor	Robert A. Koch
Title	Shared Communication Presence Information
Express Mail Label No.	EL513162266US

09/709038  
11/10/00

### APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1.  Fee Transmittal Form (e.g., PTO/SB/17)  
(Submit an original and a duplicate for fee processing)
2.  Applicant claims small entity status.  
See 37 CFR 1.27.
3.  Specification [Total Pages 30]  
(preferred arrangement set forth below)
  - Descriptive title of the invention
  - Cross Reference to Related Applications
  - Statement Regarding Fed sponsored R & D
  - Reference to sequence listing, a table, or a computer program listing appendix
  - Background of the Invention
  - Brief Summary of the Invention
  - Brief Description of the Drawings (if filed)
  - Detailed Description
  - Claim(s)
  - Abstract of the Disclosure
4.  Drawing(s) (35 U.S.C. 113) [ Total Sheets 8 ]
5.  Oath or Declaration [Total Pages 13]
  - a.  Newly executed (original or copy)
  - b.  Copy from a prior application (37 CFR 1.63 (d))  
(for continuation/divisional with Box 17 completed)
    - i.  **DELETION OF INVENTOR(S)**  
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b)
6.  Application Data Sheet. See 37 CFR 1.76

**ADDRESS TO:** Assistant Commissioner for Patents  
Box Patent Application  
Washington, DC 20231

7.  CD-ROM or CD-R in duplicate, large table or Computer Program (Appendix)
8. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
  - a.  Computer Readable Form (CRF)
  - b. Specification Sequence Listing on:
    - i.  CD-ROM or CD-R (2 copies); or
    - ii.  paper
  - c.  Statements verifying identity of above copies

### ACCOMPANYING APPLICATION PARTS

9.  Assignment Papers (cover sheet & document(s))
10.  37 CFR 3.73(b) Statement  Power of (when there is an assignee)  Attorney
11.  English Translation Document (if applicable)
12.  Information Disclosure Statement (IDS)/PTO-1449  Copies of IDS Citations
13.  Preliminary Amendment
14.  Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
15.  Certified Copy of Priority Document(s) (if foreign priority is claimed)
16.  Other: .....

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment, or in an Application Data Sheet under 37 CFR 1.76:

Continuation  Divisional  Continuation-in-part (CIP)

of prior application No. \_\_\_\_\_ / \_\_\_\_\_

Group / Art Unit: \_\_\_\_\_

Prior application information:

Examiner \_\_\_\_\_

For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

### 18. CORRESPONDENCE ADDRESS

<input checked="" type="checkbox"/> Customer Number or Bar Code Label	23370 (Insert Customer Number or Bar Code Label here)			<input type="checkbox"/> Correspondence address below
Name	JOHN S. PRATT, KILPATRICK STOCKTON LLP PATENT TRADEMARK OFFICE			
Address	1100 Peachtree Street Suite 2800			
City	Atlanta	State	GA	Zip Code
Country	USA	Telephone	(404) 815-6500	Fax
Name (Print/Type)	Geoff L. Sutcliffe			36,348
Signature	<i>Geoff L. Sutcliffe</i>			Date 11/10/00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231

# ORIGINAL

PTO/SB/17 (09-00)

 Approved for use through 10/31/2002. OMB 0651-0032.  
 U S Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

 09/709038 PRO  
 11/10/00

## FEE TRANSMITTAL for FY 2001

Patent fees are subject to annual revision.

TOTAL AMOUNT OF PAYMENT (\$ 998)

### Complete if Known

Application Number	
Filing Date	11/10/00
First Named Inventor	Robert A. Koch
Examiner Name	
Group Art Unit	
Attorney Docket No.	36968/202435

### METHOD OF PAYMENT

1.  The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to:

 Deposit Account Number 11-0855  
 Deposit Account Name KILPATRICK STOCKTON LLP

 Charge Any Additional Fee Required  
 Under 37 CFR 1.16 and 1.17

 Applicant claims small entity status  
 See 37 CFR 1.27

2.  Payment Enclosed:

 Check  Credit card  Money Order  Other

### FEE CALCULATION

#### 1. BASIC FILING FEE

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid
101 710	201 355	Utility filing fee	710
106 320	206 160	Design filing fee	
107 490	207 245	Plant filing fee	
108 710	208 355	Reissue filing fee	
114 150	214 75	Provisional filing fee	
<b>SUBTOTAL (1)</b>		(\$ 710)	

#### 2. EXTRA CLAIM FEES

Extra Claims	Fee from below	Fee Paid
Total Claims 36	-20** = 16	X 18 = 288
Independent Claims 3	- 3** = 0	X 80 = 0
Multiple Dependent		

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description
103 18	203 9	Claims in excess of 20
102 80	202 40	Independent claims in excess of 3
104 270	204 135	Multiple dependent claim, if not paid
109 80	209 40	** Reissue independent claims over original patent
110 18	210 9	** Reissue claims in excess of 20 and over original patent
<b>SUBTOTAL (2)</b>		(\$ 288)

\*\*or number previously paid, if greater. For Reissues, see above

#### 3. ADDITIONAL FEES

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid
105 130	205 65	Surcharge - late filing fee or oath	
127 50	227 25	Surcharge - late provisional filing fee or cover sheet	
139 130	139 130	Non-English specification	
147 2,520	147 2,520	For filing a request for <i>ex parte</i> reexamination	
112 920*	112 920*	Requesting publication of SIR prior to Examiner action	
113 1,840*	113 1,840*	Requesting publication of SIR after Examiner action	
115 110	215 55	Extension for reply within first month	
116 390	216 195	Extension for reply within second month	
117 890	217 445	Extension for reply within third month	
118 1,390	218 695	Extension for reply within fourth month	
128 1,890	228 945	Extension for reply within fifth month	
119 310	219 155	Notice of Appeal	
120 310	220 155	Filing a brief in support of an appeal	
121 270	221 135	Request for oral hearing	
138 1,510	138 1,510	Petition to institute a public use proceeding	
140 110	240 55	Petition to revive - unavoidable	
141 1,240	241 620	Petition to revive - unintentional	
142 1,240	242 620	Utility issue fee (or reissue)	
143 440	243 220	Design issue fee	
144 600	244 300	Plant issue fee	
122 130	122 130	Petitions to the Commissioner	
123 50	123 50	Petitions related to provisional applications	
126 240	126 240	Submission of Information Disclosure Stmt	
581 40	581 40	Recording each patent assignment per property (times number of properties)	
146 710	246 355	Filing a submission after final rejection (37 CFR § 1.129(a))	
149 710	249 355	For each additional invention to be examined (37 CFR § 1.129(b))	
179 710	279 355	Request for Continued Examination (RCE)	
169 900	169 900	Request for expedited examination of a design application	
Other fee (specify) _____			

\* Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$)

### SUBMITTED BY

Name (Print/Type)	Geoff L. Sutcliffe	Registration No. (Attorney/Agent)	36,348	Telephone	(404) 815-6530
Signature	<i>Geoff L. Sutcliffe</i>			Date	11/10/00

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

Burden Hour Statement This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comment on the burden of this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231. This form is not subject to the Paperwork Reduction Act.

## INVENTOR INFORMATION

Inventor One Given Name:: Robert A  
Family Name:: Koch  
Name Suffix:: Mr.  
Postal Address Line One:: 6085 Courtside Drive  
City:: Norcross  
State or Province:: GA  
Country:: USA  
Postal or Zip Code:: 30092  
City of Residence:: Norcross  
State or Province of Residence:: GA  
Country of Residence:: USA  
Citizenship Country:: USA

## CORRESPONDENCE INFORMATION

Correspondence Customer Number:: 23370  
Fax One:: 404.815.6555  
Electronic Mail One:: patentcorrespondence@kilpatrickstockton.com  
Electronic Mail Two:: gsutcliffe@kilpatrickstockton.com

## APPLICATION INFORMATION

Title Line One:: SHARED COMMUNICATION PRESENCE INFORMATION  
Title Line Two:: N  
Total Drawing Sheets:: 8  
Formal Drawings?:: Yes  
Application Type:: Utility  
Docket Number:: 36968/202435  
Secrecy Order in Parent Appl.?:: No

## REPRESENTATIVE INFORMATION

Representative Customer Number:: 23370  
Registration Number One:: 36348

Source:: PrintEFS Version 1.0.1

## **SHARED COMMUNICATION PRESENCE INFORMATION**

### **FIELD OF THE INVENTION**

5        This invention relates in general to the field of communications, and in particular, to the field of providing communications presence information.

### **BACKGROUND OF THE INVENTION**

10       The telecommunications industry has experienced explosive growth in recent years. A portion of this growth has been driven by the need for individuals and corporations to be in constant, if not immediate, contact with each other. In the past, individuals were satisfied using a wireline telephone that was hardwired and associated with a building or location. As society has become more mobile, users demand telephones and access to information that travels with them sparking the evolution of wireless telephone service.

15       This need to be in constant communication has aided the development of additional wireless devices, such as, standard and interactive pagers and wireless computers. Electronic mail (Email) which was initially marketed as a way to achieve a paperless environment, has grown to become an additional communications medium with users sometimes choosing to 20      send an Email message instead of or in addition to placing a voice telephone call.

Recently, wireless hand-held devices that function as a cross between a telephone and a computer have grown in popularity. These devices allow a user to receive Email and text messages, as well as data on a variety of subjects such as, for instance, stock quotes from remote sources.

The Internet is a global communications system of linked computers and file servers providing users connected to the Internet information on a practically unlimited number of subjects. Most users connect to the Internet via wireline telephone connections using a personal computer, a modem and services of an Internet Service Provider (ISP) through which access to the Internet is provided. Recently devices have become available that allow remote wireless access to the Internet.

With the multitude of communications devices available, it has become exceedingly difficult to determine which communications device is being used by a party. Choices of communications devices can include, wireline telephones, wireless telephones, pagers, Email and Internet appliances. Thus one may have to try to connect to numerous communications devices before reaching the desired party. Additionally contact attempts may be made to a party at home, work, via an instant message, or via the Internet.

Accordingly, a need exists for systems and methods for presenting the status of communications devices of a user. In addition, a need exists for systems and methods for contacting a user once their communications presence has been determined.

## **SUMMARY OF THE INVENTION**

The invention addresses the problems described above by providing systems and methods for a shared communication presence information for identifying the communications presence of a member of a communications circle. Upon determining the communications presence of a member of the communications circle, that member can be immediately

contacted. Both real time and non-real time communication can occur with a member of the communications circle.

Membership in the communications circle is established by a member completing a profile using an Internet web-based form. The profile is stored in a customer profiles database.

5 A communications server translates the profile information into a unique code number for each member's profile. A collection of code numbers completes the requirement for membership in the communications circle.

The system includes a communications initiator adapted to route a contact data message through a communications network to connect to the Internet, a communications server, a database storing information regarding members of the communications circle, and member devices adapted to connect to the Internet. For example, the communications circle will consist of members A and B. The profiles and communications circles form the basis for B's ability to identify A's communications presence status so that B can choose the best method of communication to initiate communication with A. The communications server maintains a profile of all communications equipment associated with each member. When B chooses to initiate a communication with A, the communications server checks all devices listed in A's profile to determine if those devices are available. Devices can include but is not limited to, for example, a wireline telephone, a wireless telephone, an interactive pager, electronic messaging, an interactive television (TV), a personal computer (PC) having dial-up access to the Internet or a Pocket PC. Upon completion of a check of all A's communication devices, the communications server returns to an Internet web interface a presentation indicating the communications presence of A's communications devices. The results are displayed based on

current time of day and day of week using A's profile information. B can determine the best way to contact A considering current the time of day and day of week. B has several options for contacting A including initiating a telephone call to A, sending A an instant message and/or an Email message, leaving A a voice mail message or paging A.

5 In a first embodiment, the member of the communications circle can be contacted on a wireless voice and/or Short Message Service (SMS) communications device coupled to the Internet.

In a second embodiment, the member of the communications circle can be contacted on a wireline voice device coupled to the Internet.

10 In a third embodiment, the member of the communications circle can be contacted on a wireline data device coupled to the Internet.

15 In a fourth embodiment, the member of the communications circle can be contacted on a wireless Email and/or interactive pager device coupled to the Internet.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

The accompanying drawings, which are incorporated in and form a part of the specification, illustrate preferred embodiments of the present invention and, together with the description, disclose the principles of the invention. In the drawings:

20 Figure 1 is an overview diagram of an architecture of a shared communication presence information system in accordance with a preferred embodiment of the invention.

Figure 2 is an illustrative view of a personalized Internet interface that provides a display and access to the system of Figure 1.

Figure 3 is an example of a screen display showing profile information for a member of the communications circle identified on a portion of the screen of Figure 2.

Figure 4 is a diagram of an architecture for establishing the user profiles of Figure 3.

Figure 5 is an illustration of an architecture for a wireless voice communication system 5 in accordance with the system of Figure 1.

Figure 6 is an illustration of an architecture for a wireline voice communication system in accordance with the system of Figure 1.

Figure 7 is an illustration of an architecture for a wireline data communication system in accordance with the system of Figure 1.

Figure 8 is an illustration of an architecture for a wireless Email and pager communication system in accordance with the system of Figure 1.

## **DETAILED DESCRIPTION**

Reference will now be made in detail to preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

### **I. Overview of Systems and Methods**

Figure 1 is an overview diagram of an architecture for providing a shared communication presence information system 12 in accordance with the preferred embodiment 20 of the invention. The system 12 includes a user utilizing any one of several communications initiators 14 to determine the communications presence of a member of their communications

circle. Upon determining the communications presence of a member of the communications circle, that member can be immediately contacted utilizing this system 12.

The architecture includes the communications initiator 14 adapted to connect to the Internet 16, a processor 18, for instance a communications server, a customer profiles database 5 21, an Internet Service Provider (ISP) 20 and a plurality of people and contact devices (collectively referred to as contacts) 22 reachable through the Internet 16.

The communications initiator 14 can be any type of device that can connect to the Internet 16. As shown in Figure 1, the communications initiator 14 can be a wireline telephone 24 connected to a telephone company central office 25 and a voice XML gateway 25 that provides an interface to the Internet 16, a WAP-enabled telephone 26 connected to a WAP gateway 27 providing access to the Internet 16, a two-way alpha pager 28 such as an interactive pager, and a personal computer (PC) 30 adapted to communicate directly with the Internet 16.

For the purposes of this description, the communications initiator 14 will be the PC 30 that accesses the Internet 16 through the ISP 20. Accordingly, the screen shots and interfaces shown for the communications initiator 14 are PC-based and represent those from a web browser. It should be understood that the screen shots and interfaces for the communications initiator 14 will vary with the type of device. For example, the WAP-enabled telephone 26 would have smaller and more concise displays than that of the PC 30.

The contacts or contact devices 22 include any type of communications or data device. 20 The contact devices include but are not limited to, for instance, a wireline telephone 32, an interactive television (TV) 34, a PC 36 having dial-up or DSL access, a Pocket PC 38, other suitable hand-held mobile communications or data devices, an interactive pager 40, a wireless

application protocol (WAP) device 42 and a wireless voice telephone 44. A WAP device 42 is a specialized version of a wireless telephone. The WAP device 42 includes a screen having scroll capabilities for reading text messages. For instance, a text message could state check stock quotes. A user enters a stock symbol using the keypad of the WAP device 42. The WAP 5 device 42 forwards the request to a WAP gateway 54 that serves to interface with the ISP 20 for the WAP device 42 and the contact is routed through the Internet 16. The WAP device 42 accesses the Internet 16 to retrieve the current quote from the appropriate source. The Pocket PC 38 generally encompasses a smaller sized personal computer equipment with Microsoft Windows CE and computer programs such as Microsoft Pocket Word, Pocket Excel, and Pocket Internet Explorer. In addition, Email messages can be sent and received by the Pocket PC 38 using Microsoft Pocket Inbox. The invention is not limited to these form of contact devices 22 and any suitable equipment capable of accessing the Internet 16, directly or indirectly, can be utilized.

For the contact side of the communication, the wireline telephone 32 connects to the Public Switched Telephone Network (PSTN) having Advanced Intelligent Network (AIN) 46 capabilities. The PSTN/AIN 46 couples to an IN/IP gateway 48. The IN/IP gateway 48 includes data switching equipment that translates between the telephony protocols and the Internet protocols. The IN/IP gateway 48 routes contact data messages to a secure intranet 50 that serves as a firewall to protect the PSTN 46 from potential hackers who hack into the Internet 16. The contact data messages are then routed from the secure intranet 50 to the Internet 16.

The interactive TV 34 routes to the Internet 16 via a route selected by a subscriber's ISP

20. The Pocket PC 38 and PC 36 having dial-up access couple to a central office/signal switching point 52 that switches the contact data message to the ISP 20 that connects the contact data message to the Internet 16. The wireless voice telephone 44 connects to a radio 5 tower 56 coupled to a mobile switching center (MSC) 58 equipment that routes the contact data message to wireless IN protocol network 60. The wireless IN network 60 functions similar to the advanced intelligent network utilized in wireline telecommunications. The wireless IN 60 communicates with an IN/IP gateway 62 that routes the contact data message to the Internet 16.

Figure 2 presents an illustrative view of a personalized Internet interface 70 that provides a display and an interface for accessing the system 12 of this invention. This invention is not limited to the display format shown in Figure 2. A suitable presentation format for displaying the personalized Internet interface 70 for use with this invention is a portal provided by a myway.com page available from MyWay.com and provided to Internet Service Provider BellSouth.net of Atlanta, GA. Alternatively, a traditional Internet interface can be utilized to 15 display information and provide system access.

The interface 70 can include, for instance, a communications center section 72 displaying the members of the user's communications circle 74. The members of the communications circle 74 are dynamic and can be changed. The members of the communications circle 74 are a subset of the type of contacts 22 shown in the system 12 of 20 Figure 1. The communications center 72 shows one manner of displaying contact 22 information. Any number of identifying characteristics can be used to identify members of the

communications circle 74. For instance, member of the communications circle 74 can be identified by name, picture, potential presence location and type of equipment used.

A user may choose to verify presence information for a member of their communications circle 74 by clicking or otherwise selecting that person, for instance, member 5 Gwen 76. In this example, Gwen 76 has at least a mobile telephone. An example of additional identifying information regarding Gwen 76 is shown in Figure 3.

Figure 3 is an example of a screen display of an interface 80 showing profile information 82 for Gwen 76, a member of the communications circle identified on a portion of the screen of Figure 2. The profile information 82 is displayed by clicking on tab displaying the term “My Contacts” 84 shown on the screen display 80. Any number of other features can be accessed by clicking their respective tabs, for instance, “My Calendar” 86, “My News & Information” 88, “Communications Log” 90, “My BellSouth Services” 92, “My Communications Preferences” 94 and “My Messages” 94.

By clicking on the tab My Contacts 84, a screen is opened and displays the profile information 82 for Gwen 76. Additionally, a photograph 112 of Gwen 76 can be displayed. For illustrative purposes, the profile information 82 includes the following information about Gwen 76: (1) title of Program Manager 98; (2) name of her company, Peak Communications 100; (3) her work, mobile and facsimile telephone numbers 102, 104 and 106; (4) her interactive pager address 108; and (5) her Email address 110. This profile information 82 can 20 include and resemble information contained on a traditional business card. Information listed in the profile will be gathered by the communications server 18 to determine which of the types of contact devices 22 associated with Gwen 76 are connected to the system 12 and activated or

available to receive a contact or telephone call. The communications server 18 gathers communications presence information 107 on each contact device 22 prior to displaying its current accessibility, as shown in the lower portion of the interface 80 of Figure 3.

Once the server collects communications presence information 107 on all devices 22, 5 the communication initiator 14 intelligently determines the best way to contact Gwen 76. In the example shown in Figure 3, Gwen's mobile telephone 104, interactive pager 108, voice mail for work 102, and Email 110 are active (i.e. turned on). The communications presence information 107 is preferably time of day and day of week specific. That is, the communications initiator 14 can receive information relevant for the current day. Thus, at the time of the display of the My Contacts 84 information, Gwen 76 is accessible by mobile telephone, interactive pager, voice mail and Email. Gwen's mobile telephone and interactive pager can be accessed by clicking on one of the tabs "connect" 114, 116. To connect to Gwen 76 via voice mail, clicking the tab "Click to Dial" 118 will dial to ring Gwen's 76 telephone, for instance, her work telephone 102 to leave her a voice mail message. An Email message can be sent to Gwen 76 by clicking the tab "Send E-Mail" 120 to connect to Gwen's electronic mail.

## II. Shared Communications Presence Information System Setup

### A. Establishing Profiles and Communications Circles

Figure 4 is a diagram of an illustrative architecture 200 for establishing the user profiles, 20 such as those shown in Figure 3. For simplicity, Figure 4 shows only two parties, A 204 and B 202, who are members of a communications circle 74 and wish to communicate with each

other. However, this invention is not limited to only two members of a communications circle 74.

In this example, Party A 204 and Party B 202 choose to be members of a common communications circle. To facilitate communications between A 204 and B 202, they both 5 complete a profiles form accessible on a web page or by using the personalized Internet interface 70. Parties who wish to be members of the communications circle 74 can include a variety of information on their contact devices 22 and when they are available through the contact devices 22. An example of information included in the profile for A 204 is shown below in Table 1.

Home Telephone Number	7042540010	M-F 6P- 10P Sa-Su
Work Telephone Number	7043450020	M-F 8A-5P
Mobile Telephone Number	8283334434	
SMS Address	8283334434@company.com	
Email Address	custa@bellsouth.net	
AlphaPager Address	custa@bellsouthips.net	
Mobitex Access Number	15254678	
Internet DN	7042540010	

10

Table 1.

Table 1 shows an example of possible profile data that can be stored on A 204. For example, the profile can contain telephone numbers and time of day or day of week that a member will be available at that particular telephone number.

Both A 204 and B 202 complete a profile 205, 207 that is stored in the customer profiles database 21. The communications server 18 generates a random and unique code number for each profile and assigns a code number to each profile 205, 207 stored in the customer profiles database 21. The profiles for A 204 and B 202 are stored in the customer profile database 21 that is coupled to the communications server 18. Each party's communications circle 74 includes code numbers for each member of the communications circle 74. B 202 establishes his communications circle 74 by logging into the communications server 18 to create his communications circle 74 using a form on a web page. The form asks, for instance, for the code numbers for each customer to be included in the circle 74. Table 2 below shows a sample communications circle 74 for B 202.

Code Number for A
Code Number for C
Code Number for D

Table 2.

A 204 creates a similar communications circle 75. The completed communications circles 74, 75 are stored in the customer profiles database 21. A communications circle for A 203 could include the code numbers for B, E, and F. For B 202 and A 204 to know each other's presence, they exchange code numbers with each other. Further, A 204 and B 202 identify a list of code numbers for members of their communications circle 74. For example, B

202 may want to add A 204 to their circle, as well as, for instance, members C and D, for whom  
B 202 also knows their code numbers. In addition to exchanging code numbers, parties may  
also exchange passwords, a key, or other information in order to allow access to each other's  
profile information. Thus, the communications server 18 may not add someone to a  
5 communications circle unless they have the password, key, or other information that proves the  
party has been given authorization to the party's profile information.

The communications server 18 maintains a profile of all communications equipment  
associated with each member. When B 202 chooses to initiate a communication with A 204,  
the communications server 18 checks all contact devices 22 listed in A's profile 205 to  
determine if those devices 22 are available. Upon completion of a check of all A's contact  
devices 22, the communications server 18 returns to the Internet web interface 70 a presentation  
indicating the communications presence of A's contact devices 22. The results are displayed  
based on current time of day and day of week using A's profile information. B 202 can  
determine the best way to contact A 204 considering the displayed information. B 204 has the  
option to initiate a telephone call to A 204, to send A 204 an instant message, to send an Email  
message, to leave A 204 a voice mail message, or to page A 204.

When B 202 wishes to initiate a communication with A 204, B 202 can use a PC 30 as  
the communication initiator 14. The PC 30 has dial-up access that connects to the central office  
206 and the central office 206 has a signal switching point (CO/SSP) forming part of the  
20 Advanced Intelligent Network (AIN) capabilities. The CO/SSP 206 switches the contact data  
message to the ISP 20 to connect the request to the Internet 16. The contact data message is  
routed through the Internet 16 through a secure intranet 17 to the communications server 18

which is adapted to communicate with and retrieve profile information from the customer profiles database 21. The secure intranet 17 serves as a firewall to protect the proprietary network elements such as the communications server 18 from potential illegal entry by computer hackers. The customer profiles database 21 includes profile information for both B 5 202 and A 204. Suitable servers for this invention include a Compact Service Node or Enhanced Media Resource Server by Lucent Technologies.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95

B 202 can determine the status of A 204 by using the system shown in Figure 5. When B 202 logs into the personalized Internet interface 70, the communications server 18 retrieves B's communications circle 74 using the customer profiles database 21. B's communications circle 74 contains the list of code numbers, each of which is used as a pointer to find a corresponding profile. For example, B's communications circle 74 contains A's Code Number which is used to find A's profile 205. A's profile 205 is returned to the communications server 18. The communications server 18 now knows where A 204 might be based on the time of day and/or day of week and a list of contact information contained in A's 204 profile 205. A 204 uses for instance, a PC 36, as a contact device 22. However, as mentioned above, a number of other devices can serve as contact devices 22. The PC 36 has dial-up access to the central office/signal switching point 52 that switches the contact data message to the ISP 20 to connect the contact to the Internet 16.

20 The architecture described above for establishing profiles and communications circles can be utilized for a number of communications devices as described below.

#### B. Wireless Voice Communication, SMS Communication

B 202 can determine the status of A 204 by using the system 201 shown in Figure 5.

When B 202 logs into the personalized Internet interface 70, the communications server 18 retrieves B's communications circle 74 using the customer profiles database 21. B's communications circle 74 contains the list of code numbers, each of which is used as a pointer 5 to find a corresponding profile. For example, B's communications circle 74 contains A's Code Number which is used to find A's profile 205. A's profile 205 is returned to the communications server 18. The communications server 18 now knows where A might be.

The communications server 18 sends an IS-41 LocationRequest message to the Home Location Register (HLR) 209 containing A's mobile telephone number. IS-41 is a standard protocol used in wireless applications. When a wireless telephone 44 is turned on, a request is sent to the HLR 209 alerting it that the wireless telephone 44 is activated and can accept calls. If a telephone call to the wireless telephone 44 is initiated, HLR 209 alerts the wireless telephone to ring because it is available to accept telephone calls. The HLR 209 sends an IS-41 LocationRequest Return Result back to the communications server 18, indicating whether or 15 not A's mobile telephone 44 is turned on.

If A's wireless telephone 44 is turned on, the communications server 18 now knows of the communications presence of A 204 and this status can be displayed to B 202 via the web interface 80. B 202 can thus initiate a call to A's mobile telephone 204 via an Internet Telephony PC client software that allows B's PC 30 to operate as a traditional telephone.

20 Suitable client software entitled Microsoft NetMeeting is available from Microsoft Corporation.

Alternatively, A's mobile telephone 44 can be contacted using a traditional telephone that initiates a normal voice telephone call. In yet another alternative, B 202 may be presented

with an indicator, such as a button on the web interface that permits B 202 to click the button to send an Email message to A's Short Message Service (SMS) Email address, thus sending a text message to A's mobile telephone 204. SMS is a specific instance of data communications unique to a wireless device that allows an email based text message to be sent to that device.

5 If A's wireless telephone 44 is not on or is not recognized by the HLR 209, the communications server 18 can return an option on the web interface 80 to leave A 204 a voice mail message. Alternatively, B 202 may receive a standard "out of range" announcement if a telephone call is placed to A 202.

10 **C. Wireline Voice Communication**

15 Figure 6 is an illustration of an architecture 211 for a wireline voice communication system in accordance with the system of Figure 1. The wireline telephone equipment is always connected to the network. However, while the wireline telephone is connected, A 204 may not be available to answer the wireline telephone. Thus, in checking A's communications presence, it is important to identify what time of the day and/or day of the week A 204 is available at the wireline telephone.

20 B 202 would like to initiate a communication with A 204. B 202 uses a PC 30 as the communication initiator 14. The PC 30 has dial-up access that connects to the central office/signal switching point 206 that switches the telephone call to the ISP 20 to connect the request to the Internet 16. The request routes through the Internet 16 to the communications server 18 adapted to communicate with and retrieve profile and communications circle 74, 75

information from a customer profiles database 21. The communications server 18 routes the request through the Internet 16 to the ISP 20 utilized by A 204.

The home or work telephone numbers for A 204 can be displayed to B 202 based on the current time of day and day of the week. For example, A 204 may not actually be at the 5 displayed telephone number, but A 204 has, in effect, stated a preference to B 202, by the hours listed in Table 1 as reach telephone numbers for telephone calls to a wireline telephone. Alternatively, A 204 can set a forward-to number in their profile, for instance, if A 204 is out of town. In another alternative, A 204 can run a web-based calendar application on the communications server 18 that can automatically update reach telephone numbers based on calendar events. B 202 can initiate a call to A 204 via an Internet Telephony PC client, for example, Microsoft NetMeeting. Alternatively, B 202 can initiate a traditional voice telephone call to A 204.

#### D. Wireline Data Communication

Figure 7 is an illustration of an architecture 214 for a wireline data communication system in accordance with the system of Figure 1. The architecture includes PCs 30, 36, an ISP 20 for connecting with the Internet 16, the Internet 16, communications server 18, customer profiles database 21, SCP 216, and contact devices 22 utilized by A 204. A 204 has access to a 20 number of dial-up Internet access equipment, for example, a PC 36, an Internet appliance 218, a Television (TV) browser 34, and Pocket PC 38.

The Internet appliance 218 typically includes a monitor, a keyboard or other input device, and a modem for connecting to the Internet 16 and receiving Email messages.

Normally, no processor is provided and the Internet appliance 218 does not include computer programs such as Microsoft Word. A suitable Internet appliance is model I-opener by Netpliance of Austin, Texas. Product information is available at [www.netpliance.com](http://www.netpliance.com).

WebTV Networks, Inc. a subsidiary of Microsoft Corporation makes a suitable television browser 34 for connecting to the Internet 16. Product information is available at [www.webtv.com](http://www.webtv.com). All of these devices have access to the Internet 16, browsing capabilities and connects to the ISP 20 to connect the request to the Internet 16. Once the dial-up device is connected to the Internet 16 the communications server 18 is aware of the presence of the contact device 22 and the contact devices 22 can receive Email messages or an instant message.

#### 1. DN/IP Address Setup

Figure 7 shows a an architecture 214 for establishing an Internet dial number and Internet Protocol address for the system of Figure 1 to determine the presence of the dial-up devices. B 202 uses a PC 30 as the communication initiator 14. The PC 30 has dial-up access to dial into the central office 206 having a SSP software and AIN capabilities. AIN service operates beyond just the switch, allowing communications service providers to build their own services and are not limited to services offered by the switch manufacturer. Additionally, AIN provides for triggers that interrupt processing a call into the SSP and sends the call using signaling system 7 (SS7) 220, a telephony protocol, to the service control point (SCP) 216. The SCP 216 performs a query outside of the switch and instructs the switch how to process the call.

To begin the call setup, A 204 dials-up their ISP 20 to initiate an Internet 16 session.

For instance the telephone number to call to access the ISP 20 is (404) 332-2116. The call is interrupted by an AIN feature code trigger. The dial string for the ISP 20 dial-in number is preceded by a \*XX feature code, which corresponds to the AIN feature code trigger on A's 204 telephone line, interrupting the call so that it can be processed differently. For instance, the dialing string may be, for instance, \*95,4043322116. The \*XX sequence causes an AIN Feature Code trigger resulting in a query to the SCP 216. This query contains A's 204 Internet dialing number (DN) representing the number A 204 is dialing from, for example (404) 332-1000. The SCP 216 returns a response to the SSP, indicating to the SSP to route the call to the ISP 20 and to notify the SCP 216 when the call ends. Thus a session is established with the ISP 20.

The ISP 20 assigns an Internet Protocol (IP) address to A 204. The IP address is unique to the computer attempting Internet 16 access and encompasses a stream of numbers such that the communications server 18 knows that computer 36 is on the Internet 18, and how to reach that computer 36. A sample IP address is 205.53.81.2. The Internet device, such as the computer 36 sends a message using Internet signaling protocol for data, TCP/IP 218, to the server 18 containing A's 204 Internet DN/IP address pair creating a record. For instance a record =7042540010/205.53.81.2. The PC 36 (or other Internet device) now has assigned an Internet DN/IP address pair and communications server 18 becomes aware of A's 204 record information and that A's PC 36 is connected to the Internet 16. It is now possible to send an email based text message, such as an instant message, to A 204 or send an Email message to A 204.

When A 204 terminates an Internet 16 session, the SSP sends a TCAP AIN 0.1 message to the SCP 216 containing A's Internet DN. Upon receipt of the TCAP AIN 0.1 message, the SCP 216 clears the DN/IP address pair from its database.

5           2.     Determining A's Communications Presence

In the example shown in Figure 7, A 204 could be on a number of different possible types of dial-up Internet access equipment. The communications server 18 queries the SCP 216, based on the Internet DN in A's profile, via the TCP/IP 218 to determine whether A 204 has an active IP address. If A 204 has a DN/IP address pair in the SCP 216, then A 204 has an active IP address. The IP address from the address pair is returned to the communications server 18. The communications server 18 displays to B 202 via B's PC 30 that A 204 is on-line and offers B 202 the option to send an Instant Message to A 204 or an Email to A 204.

10           E.     Wireless Email/Pager

15           Figure 8 is an illustration of an architecture 230 for a wireless Email and pager communication system in accordance with the system of Figure 1. The architecture includes B's PC 30, an ISP 20 for connecting to the Internet 16, the Internet 16, the communications server 18, customer profiles database 21, a MSC 58 coupled to a radio tower 56, and A's pager 40.

20           To determine the if A's pager 40 is accessible, the communications server 18 sends a query to the wireless data network 232. In response to this query, the wireless data network 232 queries the pager 40 to see if it is activated and can receive a page. The precise way in

which the wireless data network 232 queries the pager 40 will vary with the network 232 itself and the pager 40. As one example, when the pager 40 is an interactive pager manufactured by Research In Motion (RIM) of Waterloo, Ontario, the paging network can ping the pager 40 with an on/off message to see if it is active. The paging network uses the Mobitex Access Number, which is shown above in Table 1, to perform this pinging operation. If the pager 40 is on, then the pager 40 respond to the on/off message with an “on” reply. This querying is transparent to A 204. The wireless data network 232 then responds to the communications server 18 by informing it whether the pager 40 is activated.

The communications server 18 then takes the information learned from the wireless data network 232 to update A’s communications presence. If A’s pager 40 is on, this status is displayed to B 202 via the personalized Internet interface 70 and B 202 is given the option of sending a page to A 204.

An advantage of this invention is that a determination can be intelligently and efficiently made as to which communications equipment associated with a member of a communications circle is activated.

Another advantage of this invention is that once a determination is made that a member of a communications circle has a communications device available, that member can be immediately contacted.

The foregoing description of the preferred embodiments of the invention has been presented only for the purpose of illustration and description and is not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in light of the above teaching.

The embodiments were chosen and described in order to explain the principles of the invention and their practical application so as to enable others skilled in the art to utilize the invention and various embodiments and with various modifications as are suited to the particular use contemplated.

## CLAIMS

1        1. A method for identifying to a user an availability of members through their  
2 contact devices, comprising:  
3            storing a profile on each member, the profile identifying at least one contact device for  
4 each member;  
5            providing information on the profile for each member to the user; and  
6            tracking a communications presence of the contact device for each member, the tracking  
7 including determining the availability of the contact device for each member.

1        2. The method of claim 1, further comprising allowing the user to initiate  
2 communications with the member through the contact device.

1        3. The method of claim 1, further comprising receiving a notification that the  
2 contact device associated with each member is active.

1        4. The method of claim 3, further comprising connecting the user to the member  
2 having the active contact device.

1        5. The method of claim 1, further comprising storing a communications circle of  
2 members for each user.

1           6.     The method of claim 1, wherein determining the availability of the contact  
2     device comprises querying the contact device.

1           7.     The method of claim 1, wherein determining the availability of the contact  
2     device comprises querying a network provider associated with the contact device.

1           8.     The method of claim 2, wherein allowing the user to initiate communications  
2     with the contact device comprises connecting the user to the contact device.

1           9.     The method of claim 2, wherein allowing the user to initiate communications  
2     with the contact device comprises sending a message to the contact device.

1           10.    The method of claim 1, wherein storing the profile comprises enabling a  
2     plurality of contact devices to be stored for each member.

1           11.    The method of claim 1, wherein storing the profile comprises storing addressing  
2     information for each contact device.

1           12.    A system for facilitating communication between a user and members of a  
2     communications circle, comprising:  
3            a database for storing profiles of all members of the communications circle, each profile  
4     identifying at least one contact device for each member; and

5           a communications server for retrieving the profile from the database and for determining  
6        an availability of the contact device for each member in the communications circle, the  
7        communications server providing the profile and information on the availability of the contact  
8        device to the user upon request;  
9            wherein, from the profile and the information on the availability of the user, the user can  
10      initiate contact with any one of the members in the communications circle.

1           13.    The system of claim 12, wherein the database stores a code number for  
2        correlating the profile and communications circle information of the members.

1           14.    The system of claim 12, wherein the information on the availability of the  
2        contact device indicates if the contact device is active.

1           15.    The system of claim 12, wherein the profile includes an address for the contact  
2        device.

1           16.    The system of claim 12, wherein the communications server connects the user to  
2        one of the members in the communications circle.

1           17.    The system of claim 16, wherein the communications server connects the user to  
2        the one member of the communications circle through the Internet.

1        18. The system of claim 16, wherein the communications server connects the user to  
2        the one member of the communications circle through an email message.

1        19. The system of claim 16, wherein the communications server connects the user to  
2        the one member of the communications circle through a page sent to the one member.

1        20. The system of claim 16, wherein the contact device of the one member  
2        comprises a wireless device and the communications server connects the user to the one  
3        member of the communications through a wireless network.

1        21. The system of claim 16, wherein the one member of the communications server  
2        has an interactive television and the communications server connects the user to the interactive  
3        television of the one member.

1        22. The system of claim 16, wherein the one member of the communications circle  
2        has a personal computer with access to the Internet through an internet service provider and the  
3        communications server connects the user to the personal computer of the one member.

1        23. The system of claim 16, wherein the communications server connects the user to  
2        an Internet appliance of the one member of the communications circle.

1           24. An interface for being provided to a user to display communications presence  
2   information on a user's communications circle, comprising:  
3           a communications section for displaying the members of the user's communications  
4   circle, each member in the communications circle having at least one contact device through  
5   which each member may communicate with the user; and  
6           a profile section for displaying profile information on each member of the  
7   communications circle, the profile information identifying each member, listing contact devices  
8   associated with each member, and displaying an availability of each of the contact devices;  
9           wherein the user is able to determine which contact device is available by viewing the  
10   profile information on the members of the communications circle and can initiate contact with  
11   any member having an available contact device.

1           25. The interface of claim 24, wherein the communications section displays a name  
2   of each member in the communications circle.

1           26. The interface of claim 24, wherein the communications section displays the  
2   contact devices associated with each member of the communications circle.

1           27. The interface of claim 24, wherein the communications section has a link for  
2   allowing the user to view the profile section.

1        28. The interface of claim 24, wherein the interface includes the profile section for

2    each of the members in the communications circle.

1        29. The interface of claim 24, wherein the profile section address information for the

2    contact devices associated with each member and the availability of each contact device.

1        30. The interface of claim 24, wherein the interface further includes a contact section

2    for allowing the user to communicate with an available contact device in the user's

3    communications circle.

1        31. The interface of claim 24, wherein the interface is for display on a personal

2    computer.

1        32. The interface of claim 24, wherein the interface is for display on a wireless

2    device.

1        33. The interface of claim 24, wherein the interface is for display through a pager.

1        34. The interface of claim 24, wherein the interface is for display through a wireless

2    telephone.

1           35. The interface of claim 24, wherein the interface is for display on an interactive  
2           television.

1           36. The interface of claim 24, wherein the interface is for display on a personal  
2           digital assistant.

## **ABSTRACT**

A shared communication presence information identifies the communications presence of a member of a communications circle. Upon determining the communications presence of a member of the communications circle, that member can be immediately contacted through an activated contact device associated with the member.




Figure 1





Figure 2



**Figure 3**

Figure 4





Figure 5






Figure 6




Figure 7




Figure 8

**DECLARATION FOR PATENT APPLICATION** Original Supplemental Substitute PCT

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below), or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**SHARED COMMUNICATION PRESENCE INFORMATION****(Title of the Invention)**

the specification of which (check one)

is attached hereto

was filed on \_\_\_\_\_ as U. S. Application Serial Number or PCT

International Application Number \_\_\_\_\_

and was amended \_\_\_\_\_

(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 (a) - (d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified, by checking the box below, any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Applications			Priority Claimed		Copy Attached	
Application Number	Country	Foreign Filing Date (MM/DD/YYYY)	YES	NO	YES	NO

I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below and claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT international application(s) designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application(s) in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

Parent Application Number	Filing Date	Status (Mark Appropriate Column Below)		
		Patented	Pending	Abandoned

As a named inventor, I hereby revoke all prior powers and appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

FIRM NAME: KILPATRICK STOCKTON LLP, 1100 Peachtree Street, Suite 2800, Atlanta, Georgia 30309-4530

Attorney and/or Agent	Registration No.
Roger T. Frost	22,176
Charles Y. Lackey	22,707
Anthony B. Askew	24,154
John M. Harrington	25,592
Robert E. Richards	29,105
Donald R. Andersen	28,280
John S. Pratt	29,476
A. Jose Cortina	29,733
James L. Ewing, IV	30,630
Stephen M. Schaetzl	31,418
James Dean Johnson	31,771
Charles W. Calkins	31,814
Larry A. Roberts	31,871
Jamie L. Greene	32,467
George T. Marcou	33,014
Bernard J. Graves, Jr.	33,239
Dean W. Russell	33,452
Richard T. Peterson	35,320
Charles T. Simmons	35,359
Nora M. Tocups	35,717
Bruce D. Gray	35,799
Theodore R. Harper	35,890
Geoff L. Sutcliffe	36,348
Stephen B. Parker	36,631
Pat Winston Kennedy	36,970
Leona G. Young	37,266
Suzanne Seavello Shope	37,933
Mitchell G. Stockwell	39,389
Mary Anthony Merchant	39,771
Brenda Ozaki Holmes	40,339
Michael J. Turton	40,852
Yoncha L. Kundupoglu	41,130
Scott Zimmerman	41,390
Kimberly J. Prior	41,483

Attorney and/or Agent	Registration No.
Benjamin D. Driscoll	41,571
Alana G. Kriegsman	41,747
Theodore M. Green	41,801
J. Steven Gardner	41,772
James J. Bindseil	42,326
Heather D. Carmichael	42,389
John K. McDonald	42,860
Sima Singadia Kulkarni	43,732
Camilla Camp Williams	43,992
Christopher J. Chan	44,070
Carl B. Massey	44,224
Li K. Wang	44,393
John William Ball, Jr.	44,433
Dawn-Marie Bey	44,442
Tiep H. Nguyen	44,465
John M. Briski	44,562
Michael J. Dimino	44,657
S. Craig Hemenway	44,759
Kristin L. Johnson	44,807
J. Jason Link	44,874
Paul E. Knowlton	44,842
Charles E. Peeler	45,004
Bambi F. Walters	45,197
Cheryl L. Huseman	45,392
Shelby B. Grier	45,785
Jennifer R. Seng	45,851
Vaibhav P. Kadaba	45,865
Greg Moldafsky	46,514
J. Michael Boggs	46,563
Michael K. Dixon	46,665
Kyle M. Globerman	46,730
Tywanda L. Harris	46,758
Kristin D. Mallatt	46,895
Cynthia B. Rothschild	47,040
Joseph Bennett-Paris	47,226

I acknowledge the above-listed attorneys and agents and their firm Kilpatrick Stockton LLP represent my employer (if I am an employee and this application has been or will be assigned to my employer) or the entity with which I have contracted (if I am an independent contractor and this application has been or will be assigned to such entity) and in such cases do not represent me individually. I further acknowledge I have not established, nor will I seek to establish, any personal attorney/client relationship with Kilpatrick Stockton LLP in connection with this application and understand that, should I require legal representation, I will obtain such, at my expense, other than through Kilpatrick Stockton LLP.

Send Correspondence to: John S. Pratt, Esq. Customer No. 23370  
Kilpatrick Stockton LLP  
1100 Peachtree Street, Suite 2800  
Atlanta, Georgia 30309-4530

Direct telephone calls to: Geoff L. Sutcliffe (404) 815-6530

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor Robert A. Koch  
Inventor's signature \_\_\_\_\_ Date \_\_\_\_\_  
Residence 6085 Courtside Drive, Norcross, GA 30092  
Citizenship USA  
Post Office Address 6085 Courtside Drive, Norcross, GA 30092